



CRYSTAL • GLASS WALL











CRYSTAL GLASS WALL

Double glazing with 3" (75 mm) air space

- > Superior acoustics
- > Laboratory tested STC of 44
- > Allows optional remote-controlled horizontal blinds
- > 1/4" (6 mm) tempered glass compliant with ASTM C1048

Interlocking astragals

- > Glass panels may be mixed with Signature 800 solid panels
- > Ensures a rigid flat wall

Individual and paired panels

- > Enhanced layout flexibility
- > Stacking options: lateral, remote, or center

Automatic bottom seals

> Allows operation of partition without the use of lever or tool

Available options

- > Frame color: multiple anodizing or powder coating choices
- Multiple choices of glass finishes such as acid-etched, sand-blasted, frosted, painted, or with etched designs, etc
- > Remote-controlled electrically tilting horizontal blinds
- > ADA-compliant pass through door
- > ADA-compliant pivot closure panel
- Dry-erase white boards, porcelain boards, chalk boards, cork boards, all inset
- Manually operated top and bottom retractable seals eliminate all friction during movement of the panels





| MODELS | 240 | 241 | 242 |
|---------------|---|---|---|
| OPERATION | Single point | Individual | Paired |
| CONFIGURATION | Center | Remote/Side | Center |
| THICKNESS | 4″ (102mm) | 4″ (102mm) | 4″ (102mm) |
| STC | 44 | 44 | 44 |
| MAX. HEIGHT | 12'-3" (3734mm)* | 12′-3″ (3734mm)* | 12′-3″ (3734mm)* |
| PANEL WIDTH | Min. 12" (304mm) Max. 48 1/2" (1230mm)** | Min. 12" (304mm) Max. 48 1/2" (1230mm)** | Min. 12" (304mm) Max. 48 1/2" (1230mm)** |
| PANEL WEIGHT | 9.5lbs/sq.ft. (46.5kg per sq.m.) | 9.5lbs/sq.ft. (46.5kg per sq.m.) | 9.5lbs/sq.ft. (46.5kg per sq.m.) |
| CLOSURE | Pivot/Telescopic | Pivot/Telescopic | Pivot/Telescopic |
| SEALS | MM-1.5 | FA-2/FM-1.5/MM-1.5 | FA-2 |
| TRACK | #45-T/#72 | #23-T | #45-T/#72 |

*Higher panels available upon request if reduced width is acceptable

**Wider panels available if smaller then 12'-3" (3734mm) in height

SEALS TYPE

| MM-1.5 | Manually-operated top 1" (25mm) and bottom 1 1/2" (38mm) floor clearance | |
|--------|--|--|
| FM-1.5 | Fixed top 1" (25mm) and manually-operated bottom 1 1/2" (38mm) floor clearance | |
| FA-2 | Fixed top 1" (25mm) and automatic bottom 2" (50mm) floor clearance | |

1-800-363-3150 • moderco.com