



GLASS WALL

CRYSTAL

DOUBLE GLAZING WITH 3" (75 mm) AIR SPACE

- » Superior acoustics
- » Laboratory tested STC of 44
- » Allows optional remote-controlled horizontal blinds
- » 1/4" (6 mm) tempered glass compliant with ASTM C1048



INTERLOCKING ASTRAGALS

- » Glass panels may be mixed with Signature 800 solid panels
- » Ensures a rigid flat wall

INDIVIDUAL AND PAIRED PANELS

- » Enhanced layout flexibility
- » Stacking options: lateral, remote, or center





GLASS WALL CRYSTAL

AUTOMATIC BOTTOM SEALS

- » Allows operation of partition without the use of lever or tool

AVAILABLE OPTION

- » Frame color: multiple anodizing or powder coating choices
- » Multiple choices of glass finishes such as acid-etched, sand-blasted, frosted, painted, or with etched designs, etc
- » Remote-controlled electrically tilting horizontal blinds
- » ADA-compliant pass through door

- » ADA-compliant pivot closure panel
- » Dry-erase white boards, porcelain boards, chalk boards, cork boards, all inset
- » Manually operated top and bottom retractable seals eliminate all friction during movement of the panels



GLASS WALL

Models	240	241	242
Operation	Single point	Individual	Paired
Configuration	Center	Remote/Side	Center
Thickness	4" (102mm)		
STC	44		
Max.Height	12'-3" (3734mm)*		
Panel width	Min. 12" (304mm) Max. 48 1/2" (1230mm)**		
Panel weight	9.5lbs/sq.ft. (46.5kg per sq.m.)		
Closure	Pivot/Telescopic		
Seals	MM-1.5	FA-2/FM-1.5/MM 1.5	FA-2
TRACK	#45-T/#72	#23-T	#45-T/#72

*Higher panels available upon request if reduced width is acceptable

**Wider panels available if smaller than 12'-3" (3734mm) in height



GLASS WALL

Seals	
Operation	Manually-operated top 1" (25mm) and bottom 1 1/2" (38mm) floor clearance
Configuration	Fixed top 1" (25mm) and manually-operated bottom 1 1/2" (38mm) floor clearance
Thickness	Fixed top 1" (25mm) and automatic bottom 2" (50mm) floor clearance