


Technical Data Sheet Crystal 240 – STC 44



Features & Options

Standard Features

- Manually-operated single-point individual-panel glass movable partition.
- STC 44.
- 102 mm [4"] nominal thickness. 1230 mm [48 1/2"] maximum width.
- Clear-anodized steel-reinforced aluminum frame.
- Protective trims on the entire perimeter.
- Combination aluminum and vinyl tongue and groove vertical sound seals between panels.
- Final closure by telescopic jamb.
- Type MM-1.5 horizontal seals:
 - top and bottom retractable seals
 - Manually-operated, simultaneously-activated top and bottom seals
 - bottom seals provide a 38 mm [1 1/2"] floor clearance
- Clear-anodized 6063-T6 alloy aluminum track.
- Each panel supported by one carriers made up of four vertically-aligned precision-ground hardened steel ball bearing wheels with nylon tires.
- 6 mm [1/4"] clear tempered glass faces.

- Maximum height : 3733 mm [12'-3"].

Optional Features and Accessories

- Powder-coated frame and/or track.
- 11 ga. steel track, painted white.
- Ultra-clear or painted glass.
- Battery-powered electrically tilting blinds operated by remote control.
- Inset white marker boards / chalk boards / natural cork tack boards.
- Chalk tray.
- Acoustical or non-acoustical pocket door.
- Final closure by ADA-compliant pivot panel.

Pivot panel options:

- panic bar
- panic bar with lockable lever
- deadbolt lock

Optional Features and Accessories (cont'd)


- ADA-compliant u-shaped pass door with flush pulls and roller latch.

Pass door options:

- concealed automatic closer
- panic bar (concealed automatic closer included)
- panic bar with lockable lever (concealed automatic closer included)
- self-luminous "Running Man" exit sign with green faceplate (standard outside USA, optional in USA) *
- photoluminescent "EXIT" sign with red faceplate (standard in USA, optional elsewhere) *
- photoluminescent "EXIT" sign with green faceplate (optional) *
- self-luminous "EXIT" sign with red faceplate (optional) *
- self-luminous "EXIT" sign with green faceplate (optional) *
- deadbolt lock *

* An exit sign and a deadbolt lock will not be installed together on the same door.

Horizontal Seals



Type MM-1.5


Floor clearance : 38 mm [1 1/2\"]

Operating tolerances :

+0 mm / -19 mm [+0\" / -3/4\"]


(+0 mm / -12 mm [+0\" / -1/2\"] if the partition has a pass through door)

Track Options




#45-T aluminum track

Standard for partitions up to a height of 4648 mm [15'-3"].



#45-T aluminum track with optional hanger bracket



Hanger bracket required for installations where the topmost nuts cannot be used for adjustment.



#72 steel track with hanger bracket


Optional for partitions up to a height of 4648 mm [15'-3"].

Elevation




- 1- Telescopic closure panel
- 2- Electrically tilting blinds operated by remote control (optional)
- 3- Work surfaces (optional)
- 4- Marker tray (optional)
- 5- Telescopic closure panel with rack and pinion mechanism (optional)
- 6- Pivot panel (optional)
- 7- U-shaped pass door (optional)

Plan Views






Telescopic closure panel




Pivot closure panel

Horizontal Sections




6 End cap


Typical Layouts



Wall to wall – telescopic closure




Wall to wall – pivot closure




Pocket

Typical Layouts (cont'd)



Pocket and PN-83 non-acoustical pocket door
(partition seals to back of pocket)



Pocket and PA-82 acoustical pocket door
(partition seals to face of pocket door)